



Digital Multimeter 1330

Digital Multimeter 1330	
DC VOLTAGE MEASUREMENT	
Range	$\pm 199.99\text{mV}$, $\pm 1.9999\text{V}$, $\pm 19.999\text{V}$, $\pm 199.99\text{V}$, $\pm 600\text{V}$, 5 Ranges
Accuracy	$\pm(0.03\%+4\text{d})$
Input Impedance	$10\text{M}\Omega$
AC VOLTAGE MEASUREMENT (AC or AC + DC True RMS)	
Range	199.99mV , 1.9999V , 19.999V , 199.99V , 500V , 5 Ranges
Accuracy	$199.99\text{mV}\sim 199.99\text{V}$ 4 Ranges $45\text{Hz}\sim 2\text{KHz} \pm(0.5\%+15\text{d})$, $2\text{KHz}\sim 10\text{KHz} \pm(1\%+15\text{d})$, $10\text{KHz}\sim 20\text{KHz} \pm(2\%+15\text{d})$, $20\text{KHz}\sim 50\text{KHz} \pm(5\%+30\text{d})$, 500V Range $45\text{Hz}\sim 1\text{KHz} \pm(0.5\%+15\text{d})$
Input Impedance	$10\text{M}\Omega//100\text{pF}$
DC CURRENT MEASUREMENT	
Range	$\pm 199.99\ \mu\text{A}$, $\pm 1.9999\text{mA}$, $\pm 19.999\text{mA}$, $\pm 199.99\text{mA}$, $\pm 1999.9\text{mA}$, $\pm 19.999\text{A}$, 6 Ranges
Accuracy	$199.99\ \mu\text{A}\sim 199.99\text{mA}$ 4 Ranges $\pm(0.2\%+2\text{d})$, $1999.9\text{mA}\sim 19.999\text{A}$ 2 Ranges $\pm(0.3\%+2\text{d})$
Protection	2A 250V DC or RMS [Fuse Protected] for $199.99\ \mu\text{A}\sim 1999.9\text{mA}$
AC CURRENT MEASUREMENT(AC or AC + DC True RMS)	
Range	$199.99\ \mu\text{A}$, 1.9999mA , 19.999mA , 199.99mA , 1999.9mA , 19.999A , 6 Ranges
Accuracy	$199.99\ \mu\text{A}\sim 199.99\text{mA}$ 4 Ranges $45\text{Hz}\sim 2\text{KHz} \pm(0.5\%+15\text{d})$, $2\text{KHz}\sim 10\text{KHz} \pm(1\%+15\text{d})$, $10\text{KHz}\sim 20\text{KHz} \pm(2\%+15\text{d})$, $1999.9\text{mA}\sim 19.999\text{A}$ 2 Ranges $45\text{Hz}\sim 2\text{KHz} \pm(0.5\%+15\text{d})$
Protection	2A 250V DC or RMS [Fuse Protected] for $199.99\ \mu\text{A}\sim 1999.9\text{mA}$
OHM MEASUREMENT	
Range	$199.99\ \Omega$, $1.9999\text{K}\Omega$, $19.999\text{k}\Omega$, $199.99\text{K}\Omega$ $1.9999\text{M}\Omega$, $19.999\text{M}\Omega$, 6 Ranges
Accuracy	$199.99\ \Omega$ Range $\pm(0.1\%+4\text{d})$ $1.9999\text{K}\Omega\sim 1.9999\text{M}\Omega$ 4 Ranges $\pm(0.1\%+2\text{d})$ $19.999\text{M}\Omega$ Range $\pm(0.25\%+2\text{d})$
DIODE TEST	YES
GENERAL	
Display	0.5" , 4 1/2 Digits Green LED Display
Power Source	ACV 115V / 230V , $\pm 10\%$, 60Hz/50Hz
Dimension	262(W) x 85(H) x 270(D)mm
Net Weight	1.5kg
Accessories	ACS-018 x 1 , Operation Manual x 1